

SE



Bruciatore automatico di gasolio (pompa ad ingranaggi Danfoss)
Controllo elettronico di fiamma
Termostato di sicurezza
Presse per collegamento a termostato, umidostato o timer (solo predisposizione per SE 60)
Cavo alimentazione elettrica con spina
Camera di combustione in acciaio inox
Scambiatore di calore con raccordo fumario antivento
Struttura esterna in doppia lamiera d'acciaio per isolamento termo-acustico
Post-ventilazione di raffreddamento della camera di combustione

Automatic built-in oil burner (Danfoss gear pump)
Electronic flame-control
Safety thermostat
Set to be connected to a thermostat or a humidistat or a timer (only possibility for SE 60)
Power cord with plug
Stainless steel combustion chamber
Heat exchanger with counter flow wind chimney connector
Double skinned combustion chamber for thermo-acoustic insulation and safe low surface temperature
Automatic post ventilation of unit

modello - model	SE 60	SE 80	SE 100	SE 160	SE 280
codice - code	02SE10	02SE04	02SE01	02SE02	02SE03
potenza termica max - max heating power (kW)	17,4	23,3	29,1	46,5	81,4
	(kcal/h)				
portata aria - air output	550	1.200	1.500	1.800	3.300
	(m ³ /h)				
salto termico - temp. rise	75,2	47	50	64	62
	(°C)				
consumo gasolio - oil consumption	1,47	1,96	2,45	3,92	6,86
	(kg/h)				
Ø camino - flue Ø	120	150	150	150	150
	(mm)				
Ø guaina uscita aria - outlet hose Ø	-	-	350	350	400
	(mm)				
potenza elettrica ass. - electrical power	300	350	350	480	1.140
	(W)				
alimentazione elettrica - power supply	230, 1, 50	230, 1, 50	230, 1, 50	230, 1, 50	230, 1, 50
	(V, ~, Hz)				
capacità serbatoio - tank capacity	40	41	65	65	105
	(l)				
prezzo - price	887,00	1.180,00	1.485,00	1.715,00	2.105,00
	(Euro)				



Raccordo in lamiera collegamento a guaina
Metal sheet adapter for flexible air duct connection

Cod.	Mod.	Euro
02AC03	SE 100-160	88,00
02AC04	SE 280	139,00



Guaina flessibile bicomposita 6 m: 1,5 m in neoprene verde (resistente a 150 °C) e 4,5 m in PVC giallo (resistente a 100 °C)
Flexible air duct 6 m long: 1,5 m of green neoprene (resistant up to 150 °C) and 4,5 m of yellow PVC (resistant up to 100 °C)

Cod.	Mod.	Euro
02AC347	SE 100-160	362,00
02AC348	SE 280	399,00

Altri accessori pagg. 14-15
Other accessories pages 14-15

Pesi e misure a pag. 16
Weights and dimensions page 16

